


ULTRAFAST SWITCHING RECTIFIER




Major Ratings and Characteristics

Characteristics	10DF.	Units
$I_{F(AV)}$	1	A
$V_{RRM}$ range	100 to 800	V
$I_{FSM}$	34	A
$V_F$ @ 1 A, $T_J=25^\circ\text{C}$	1.2	V
$t_{tr}$ @ $T_J=25^\circ\text{C}$	100	ns
$T_J$ range	-65 to 150	$^\circ\text{C}$

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound
- Void-free Plastic in DO-41 package
- 1.0 ampere operation @  $T_A = 55^\circ\text{C}$  with no thermal runaway
- Exceeds environmental standards of MIL-STD-19500/228
- Ultra Fast switching for high efficiency



## Voltage Ratings

Part Number	$V_{RRM}$ , maximum peak reverse voltage V	$V_{DC}$ , maximum blocking voltage V	$I_{RRM}$ 100°C μA
10DF1	100	100	500
10DF2	200	200	
10DF4	400	400	
10DF6	600	600	
10DF8	800	800	

## Maximum Ratings and Electrical Characteristics

Parameters	10DF.	Units	Conditions
$I_{F(AV)}$ Maximum Average Forward Current	1	A	@ $T_A = 55^\circ\text{C}$ , 3/8" lead length, 60Hz resistive or inductive load
$I_{FSM}$ Peak Forward Surge Current	34	A	8.3ms single half sine waves superimposed on rated load (JEDEC Method)
$V_{FM}$ Max. Instantaneous Forward Voltage	1.2	V	@ 1A
$I_{RM}$ Maximum DC Reverse Current at Rated DC Blocking Voltage	10	μA	$T_J = 25^\circ\text{C}$
	500		$T_J = 100^\circ\text{C}$
$t_{rr}$ Reverse Recovery Time	100	ns	$I_F = 0.5\text{A}$ , $I_R = 1.0\text{A}$ , $I_{rr} = 0.25\text{A}$
$C_J$ Typical Junction Capacitance	170	pf	@ 1MHz applied reverse voltage of $4.0V_{DC}$
$R_{thJA}$ Max. Junction Thermal Resistance	115	°C/W	lead length 0.375"(9.5mm) P.C.B. mounted
$T_J$ Operating Temperature Range	-65 to 150	°C	
$T_{stg}$ Storage Temperature Range	-65 to 150	°C	
wt Approximate Weight	0.3(0.013)	g(oz)	
Case Style	DO-204AL(DO-41)		JEDEC molded plastic

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60Hz, resistive or inductive load.




Fig. 1 - Reverse Recovery Time Characteristic and Test Circuit Diagram




Fig. 2 - Forward Characteristic




Fig. 6 - Forward Current Derating Curve




Fig. 3 - Typical Junction Capacitance





Fig. 4 - Forward Surge Characteristic

**TAPING SPECIFICATIONS FOR AXIAL LEAD**

Axial lead devices are packed in accordance with EIA standard RS-296-E and specifications given below.

COMPONENT OUTLINE	COMPONENT PITCH A	INNER TAPE PITCH B	CUMULATIVE PITCH TOLERANCE
	DO-41	± 0.5mm	
	5.0mm	52.0mm	1.0mm/20pitch



ITEM	SYMBOL	SPECIFICATIONS (mm)	SPECIFICATIONS (inch)
Component alignment	Z	1.2max	0.048max
Tape width	T	6.0 ± 0.4	0.236 ± 0.016
Exposed adhesive	E	0.8max	0.032max
Body eccentricity	L1-L2	1.0max	0.040max
Reel outside diameter	D	330.0	13.0
Reel inner diameter	D <sub>i</sub>	85.7 ± 0.3	3.375 ± 0.012
Feed hole diameter	D <sub>o</sub>	16.6 ± 0.4	0.655 ± 0.016
Reel width	W	79.0 ± 1.0	3.110 ± 0.040

NOTES: 1. Each component lead shall be sandwiched between tapes for a minimum of 3.2mm (0.126")  
 2. The reel width 'w' FOR 26mm Taping is 50.0 ± 1.0mm (1.97" ± 0.040")